

**Feast Watson Commercial Industrial Timber Oil**

**AU\_DW02467**

Part A	702W0194
--------	----------

<b>Description</b>
Feast Watson Commercial Industrial Timber Oil is a lightly pigmented, penetrating oil-based exterior oil. The product is not a flammable liquid; it is combustible, and hence not classified as Dangerous Goods.





<b>Features</b>
<ul style="list-style-type: none"> <li>• Lightly pigmented penetrating oil.</li> <li>• Combustible, instead of flammable.</li> </ul>

<b>Benefits</b>
<ul style="list-style-type: none"> <li>• Gives timber a natural look.</li> <li>• Not classified as a Dangerous Goods</li> </ul>

<b>Uses</b>
For all exterior timber.

<b>Precautions And Limitations</b>
Do not apply this product in temperatures below 10°C or when rain or heavy dew is expected during the drying period. In hot temperatures, do not apply in direct sunlight and coat in the shade.

<b>Performance Guide</b>			
<b>Weather</b>	For exterior use.	<b>Salt</b>	Unaffected by splash or spillage.
<b>Heat Resistance</b>	Up to 120C.	<b>Water</b>	Good water repellency.
<b>Solvent</b>	Resists mineral turpentine and similar solvents.	<b>Abrasion</b>	Good resistance to foot traffic.
<b>Acid</b>	N/A	<b>Alkali</b>	N/A

Typical Properties																											
Gloss Level	Matt	Colour	Lightly pigmented																								
Components	1	Number Of Coats	2																								
Toxicity	Lead-free	V.O.C. Level	<605g/L																								
Touch Dry	4 hours																										
Clean Up Description	Mineral turpentine To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.																										
Application Method	 Air Spray  Brush  Roller  Pad																										
Application Conditions	<table border="0" style="width: 100%;"> <tr> <td style="text-align: center;"><b>Solids By Volume</b></td> <td style="text-align: center;">24</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">Min</td> <td style="text-align: center;">Max</td> <td style="text-align: center;">Recommended</td> </tr> <tr> <td>Wet Film Per Coat (microns)</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Dry Film Per Coat (microns)</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Recoat Time (min)</td> <td colspan="2" style="text-align: center;">12 hours</td> <td></td> </tr> <tr> <td>Theoretical Spread Rate (m<sup>2</sup>/L)</td> <td></td> <td></td> <td style="text-align: center;">10</td> </tr> </table>			<b>Solids By Volume</b>	24				Min	Max	Recommended	Wet Film Per Coat (microns)				Dry Film Per Coat (microns)				Recoat Time (min)	12 hours			Theoretical Spread Rate (m <sup>2</sup> /L)			10
<b>Solids By Volume</b>	24																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)																											
Dry Film Per Coat (microns)																											
Recoat Time (min)	12 hours																										
Theoretical Spread Rate (m <sup>2</sup> /L)			10																								
Typical Properties Notes	<p><b>DRYING TIME</b> Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times.</p> <p><b>COVERAGE</b> Coverage rates are subject to variation depending on condition of timber, timber species and timber porosity.</p>																										

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> <li><b>NEW TIMBER</b> Allow new timber to weather in its final position for 4 - 6 weeks. Prepare timber for coating with Feast Watson Woodclean as per the instructions. For best results, lightly sand the surface to remove any grain raise. Remove all sanding dust before coating.</li> <li><b>WEATHERED TIMBER</b> Prepare weathered or grey timber by cleaning thoroughly with Woodclean as per the instructions. Sanding may be required to remove stains and restore deteriorated surfaces. Remove all sanding dust before coating.</li> <li><b>PREVIOUSLY COATED TIMBER</b> Timber coated with stain or oil can be coated with Feast Watson Comercial Oil after the surface has weathered. Test if the surface is ready by sprinkling water onto the timber: if the water absorbs into the timber it is suitable for coating. If the water beads, further weathering, sanding or stripping is required. Painted or varnished surfaces need to be taken back to bare timber by stripping or sanding. Prepare timber for coating with Woodclean as per the instructions.</li> </ul>
Application Procedure And Equipment	<ul style="list-style-type: none"> <li>Stir thoroughly with a broad paddle before and during use. Apply liberally along the length of the board including exposed edges and end grain using a brush, roller, spray or applicator pad. If applying with a roller or spray, back brush the coating to ensure even penetration. Work along 3 - 4 planks at a time, in the direction of the grain. Ensure edges and end grain are fully coated. Apply two coats allowing 12 hours drying between coats.</li> <li><b>MAINTENANCE</b> Re-apply as the timber changes colour or when water repellency diminishes due to weathering. Follow surface preparation instructions.</li> </ul>

Health And Safety			
<b>MSDS Number</b>	DLXGHSEN000688	<b>Using Safety Precautions</b>	Combustible liquid. May be harmful if swallowed and enters airways. May cause an allergic reaction. May cause drowsiness and dizziness. Keep out of reach of children. Read the label before opening or using. Keep away from all sources of ignition – No smoking. Keep container tightly closed. Avoid breathing mist, vapours or spray. Use only outdoors or in a well ventilated area. Wear protective clothing, gloves, eye/face protection and a suitable respirator as required. Contaminated clothing should not be allowed out of the workplace. Wash contaminated clothing before re-use. Store locked up. Store in a well ventilated place, away from oxidising agents and foodstuffs. Keep cool. Do not empty into drains.
<b>Health Effects</b>	<p><b>INHALATION</b> Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If breathing laboured and patent cyanotic (blue), ensure airways are clear and have a qualified person give oxygen through a face mask. If breathing has stopped, apply artificial respiration at once. In the event of cardiac arrest, apply external cardiac massage. Seek immediate medical assistance.</p> <p><b>SKIN CONTACT</b> If skin contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, blistering or irritation occurs, seek medical assistance.</p> <p><b>EYE CONTACT</b> If in eyes, wash out immediately with water, Seek medical attention.</p> <p><b>INGESTION</b> Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by mouth to an unconscious patient. If vomiting occurs, give further water. Seek medical advice.</p>	<b>Flammability</b>	Combustible.
<b>Fire Suppression</b>	If material is involved in a fire, use water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder).	<b>Protective Equipment</b>	Wear protective clothing, gloves, eye/face protection and a suitable respirator as required.
<b>Storage</b>	Keep out of reach of children. Store locked up. Store in a well ventilated place, away from oxidising agents and foodstuffs.	<b>Disposal</b>	Do not empty into drains.
<b>In the case of emergency, please call 1800 033 111</b>			

Transport And Storage	
<b>Pack A</b>	702W0194
<b>Size</b>	<b>Weight</b>
10L	9.4kg
200L	190kg

**Disclaimer**

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.  
 DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427

Version 2.0 of Woodcare datasheet AU\_DW02467 approved on Thursday, 1 February 2018 2:11:40 AM (UTC)